

Technical Specifications



SPECIFICATIONS	PRONTO
Operating Environment	<ul style="list-style-type: none"> • Operating temperature range: 0 to 45 degrees Celsius • Humidity: <95% (non-condensing) • Transport temperature range: -20 to 60 degrees Celsius
Power	<ul style="list-style-type: none"> • Battery pack: Alkaline 2 x AAA or 5VDC .3A power supply
Paging Transmitter	<ul style="list-style-type: none"> • Output power: 71.83 dBµV/m at 3 meters. • Frequency Range: 433-470 MHz • Bandwidth: 445.0 kHz • Modulation: FSK (Frequency Shift Keying) • Deviation: 3.75 kHz • OTA Baud rate: 1200 • Antenna: Internal antenna
Supported Paging Protocols	<ul style="list-style-type: none"> • POCSAG
User Interface	<ul style="list-style-type: none"> • 1 or 6 Push Buttons • Connector for Use with LRS Programmer • Buzzer
Regulatory Certifications	<ul style="list-style-type: none"> • United States and Territories: FCC Part 15.231 • FCC Part 15 Subpart C:2008 • ANSI C63.4:2009 • European Community: EN 60950-1:2006 +A11:2009 +A1:2010
Dimensions & Weight	<ul style="list-style-type: none"> • Dimensions: 4 (diameter) inches x 1 (height) inch • Weight: 0.3 lb

