



Technical Specifications



SPECIFICATIONS	RX - E 4 6 7
Operating Environment	<ul style="list-style-type: none"> • Operating temperature range: 0 to 45 degrees Celsius • Humidity: <95% (non-condensing) • Transport temperature range: -20 to 60 degrees Celsius
Power	<ul style="list-style-type: none"> • Alkaline 1 x AAA • Battery charger power supply: n/a
Paging Receiver	<ul style="list-style-type: none"> • Frequency Range: 413 MHz - 470 MHz • Modulation: FSK (Frequency Shift Keying) • OTA Baud rate: 512/1200/2400 • Antenna: Internal antenna
Supported Paging Protocols	<ul style="list-style-type: none"> • POCSAG
User Interface	<ul style="list-style-type: none"> • LCD display, monochrome, 128x64 dots • 3 Push Buttons • Vibration motor • Buzzer
Regulatory Certifications	<ul style="list-style-type: none"> • United States and Territories: 47 CFR FCC Part 15 Subpart B (Class B) • ANSI C63.4:2009 • European Community: EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2010 • EN 55022:2006 Class B • EN 300 220-1 v2.3.1 • EN 301 489-1 v1.9.2:2011 • EN 61000-4-2:2009 • EN 61000-4-3:2010
Dimensions & Weight	<ul style="list-style-type: none"> • Dimensions: 2.5 x 1.77 x .75 (height) inches • Weight: 0.2 lb

